


2/4-Port USB KVM Switch

CS72U/CS74U

The CS72U / CS74U 2/4-Port USB KVM Switch is a desktop control unit that allows users to access two or four computers from a single KVM console (keyboard and mouse, audio and VGA monitor).

With the CS72U / CS74U, you can access computers conveniently using port selection pushbuttons located on the unit's front panel.


Setup is fast and easy; simply plug cables into their appropriate ports. There is no software to configure, no installation routines, and no incompatibility problems. Since the CS72U / CS74U intercepts keyboard input directly, it will work on multiple computing platforms.



Features

- One VGA console controls two (CS72U) or four (CS74U) USB VGA interface computers
- Computer selection via front panel pushbuttons
- Multiplatform support – Windows, Linux and Mac
- Audio Enabled – full bass response provides a rich experience for 2.1 channel surround sound systems
- Superior video quality – 2048 x 1536; DDC2B
- Supports USB hot-plugging
- Bus-powered*

Note: The CS72U / CS74U is bus-powered, which draws power from the connected PCs. To provide enhanced power via the built-in power jack, it is required that you use a compatible ATEN power adapter. Please contact your ATEN dealer or Technical Support for detailed information.



Specifications

	CS72U	CS74U
Computer Connections	2	4
Port Selection	Front Panel Pushbuttons	
Connectors		
Console Ports	Keyboard: 1 x USB Type-A Female (Black) Video: 1 x HDB-15 Female (Blue) Mouse: 1 x USB Type-A Female (Black) Microphone: 1 x mini stereo Jack Female (Pink) Speaker: 1 x mini stereo Jack Female (Green)	
KVM Ports	2 x SPHD-18 Female (Green)	4 x SPHD-18 Female (Green)
Power	1 x DC 5V Jack Note: Please contact your ATEN dealer or Technical Support for the compatible ATEN power adapter.	
Switches		
Selected	2 x Pushbutton	4 x Pushbutton
LEDs		
On Line/Selected	2 (Orange)	4 (Orange)
USB Link	2 (Green)	4 (Green)
Video	2048 x 1536 @ 60 Hz; DDC2B	
Power Consumption	DC5V: 0.142W	DC5V: 0.177W
Environmental		
Operating Temperature	0 – 50°C	
Storage Temperature	-20 – 60°C	
Humidity	0 – 80% RH, Non-condensing	
Physical Properties		
Housing	Metal + Plastic	
Weight	0.45 kg	0.64 kg
Dimensions (L x W x H)	13.00 x 7.65 x 4.40 cm	20.00 x 7.65 x 4.40 cm

* Product specifications and appearance are subject to change without notice.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datung Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com

Product information is subject to change without prior notice.

Released: 10/2024 V4.0

© Copyright 2024 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.

