



F121 Single Console

1080p
Full HD



Drawer Features & Display Benefits

- ▶ 1U 21" widescreen LCD console drawer
- ▶ Support Full HD with 1080p resolution
- ▶ Green LED-backlit panel technology
- ▶ 104-key keyboard with either touchpad or trackball
- ▶ MAC or SUN Micro keyboard options available
- ▶ New enhanced aesthetics with molded front handle
- ▶ Front USB port for device access (USB Hub KVM only)

Options

- 3G / HD / SD-SDI Broadcast-grade input (w/ speaker)
- HDMI (w/ speaker)
- DC power : 12V / 24V / 48V / 125V / 250V

Ordering Information	Standard (left side open)	Option (right side open)
Model	F121	F121R

Specifications

• LCD Panel

Manufacturer : **AUO**
 Size (diagonal) : 21.5" widescreen TFT
 Max resolution : 1920 x 1080
 Brightness (cd/m2) : 250
 Backlight : LED
 Colors : 16.7 M
 Contrast ratio (typ) : 1000 : 1
 Viewing angle (H/V) : 170° x 160°

Active area (mm) : 477 x 268
 MTBF (hrs) : 30,000
 Video input : Standard - DVI-D
 (single only) Option - HDMI (bundle speaker x 2)

• **Speaker :** Built-in Dual Stereo Speakers
 (HDMI only) 2W x 2

• **Casing Color :** Black (RAL 9005)

• **Power Input :** Auto-sensing 100 to 240VAC,
 50 / 60Hz

• Power Consumption (single console)

Sreen on : Max. 32W
 Power saving mode : Max. 4W
 Power button on : Max. 1W

• Environmental

Operating temperature : 0 to 55°C degree
 Storage temperature : -20 to 60°C degree
 Operating humidity : 20~90%, non-condensing
 Storage humidity : 5 ~90%, non-condensing
 Operating altitude : 16,000 ft
 Non-operating altitude : 40,000 ft
 Shock : 10G acceleration (11ms duration)
 Vibration : 5~500Hz 1G RMS random vibration

• Regulatory

Safety : FCC & CE certified
 Environmental : RoHS2 & REACH compliant

• Weight (single console)

Net : 14.7 kgs / 32.3 lbs
 Gross : 18.9 kgs / 41.6 lbs

• Dimensions (single console)

Product : 441.6 x 670 x 44 mm / 17.4 x 26.4 x 1.73 inch
 Packing : 595 x 860 x 140 mm / 23.4 x 33.9 x 5.5 inch


Console Cable

CX-6


6 feet DVI-D console cable (bundle)
 - DVI-D + USB, server end
 - DVI-D + DB15 (USB KB & MS),
 console port

Standard Keyboard

Ge G keyboard integrated with touchpad



Gb G keyboard integrated with trackball



Supporting layouts

America		United States			
EMEA					
	United Kingdom	Germany	France	Spain	Norway
	Italy	Russia	Switzerland	Netherlands	Portugal
Asia					
	China	Japan	Korea	Arabia	Turkey

Keyboard Options

* US layout only

Me Mac keyboard with touchpad



Se S keyboard with touchpad

Mb Mac keyboard with trackball

Sb S keyboard with trackball



1U 21" FHD LCD KVM Drawer



- Dimensions (with KVM)**
 Product : 441.6 x 770 x 44 mm / 17.4 x 30.3 x 1.73 inch
 Packing : 595 x 860 x 140 mm / 23.4 x 33.9 x 5.5 inch
 - Weight**
 Net : 15.5 kgs / 34.1 lbs
 Gross : 21.4 kgs / 47.1 lbs
 - Power Consumption with KVM integration :**
 Screen on : Max. 62W
 Power saving mode : Max. 34W
 - Casing Color :** Black (RAL 9005)
- * For details, please refer to our KVM rear kit user manuals.

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-MUKVM-KIT.pdf

For right side open - Add **R** at the end of the model no.
sample : F121-MUIP3224R

Matrix Cat6 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	1	1	-	F121 - MUIP1613	F121 - MUIP3213
	1	1	2	-	F121 - MUIP1624	F121 - MUIP3224
	1	1	0	-	F121 - MU1602	F121 - MU3202
	1	2	0	-	F121 - MU1603	F121 - MU3203
	1	3	0	-	F121 - MU1604	F121 - MU3204

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-UKVM-KIT.pdf

Combo Cat6 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	0	1	F121 - UIP802	F121 - UIP1602	F121 - UIP3202
	1	1	0	F121 - U802	F121 - U1602	F121 - U3202
	1	0	0	F121 - U801	F121 - U1601	F121 - U3201

Cat6 KVM Dongle : DG-100S (VGA-USB) / DG-100 (VGA-PS/2) / DG-100SD (DVI-USB)

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-MKVM-KIT.pdf

For right side open - Add **R** at the end of the model no.
sample : F121-S1601R

Matrix DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	1	1	F121 - MIP813	F121 - MIP1613	-
	1	1	2	F121 - MIP824	F121 - MIP1624	-
	1	1	0	F121 - M802	F121 - M1602	-
	1	2	0	F121 - M803	F121 - M1603	-
	1	3	0	F121 - M804	F121 - M1604	-

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-SKVM-KIT.pdf

Combo DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	0	1	F121 - IP802	F121 - IP1602	-
	1	1	0	F121 - 802	F121 - 1602	-
	1	0	0	F121 - S801	F121 - S1601	-

Combo DB-15 KVM Cable : CE-6 / 10 / 15 (6, 10 or 15 ft)

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-DVIKVM-KIT.pdf

For right side open - Add **R** at the end of the model no.
sample : F121-1201DR

DVI-D KVM	Local	Remote	IP	12-port	-	-
	1	0	0	F121 - 1201D	-	-

DVI-D KVM Cable : CI-6 / 15 (6 or 15 ft)

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-USBKVM-KIT.pdf

For right side open - Add **R** at the end of the model no.
sample : F121-801HR

USB Hub DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	0	1	F121 - IP802H	F121 - IP1602H	-
	1	1	0	F121 - 802H	F121 - 1602H	-
	1	0	0	F121 - 801H	F121 - 1601H	-

USB KVM Cable : CB-6 / 10 / 15 (6, 10 or 15 ft)