

**VIDEO WALLS VIDEO PROCESSORS VIDEO MATRIX SWITCHES EXTENDERS SPLITTERS WIRELESS CABLES & ACCESSORIES** 

## HDM-SWITCHPRO-VW4


Advanced Dual Screen Multiviewer Matrix, 2X2 Video Wall Function with Audio & Fron Panel IR and RS232 Control

## **VIDEO WALL PROCESSOR**



### **KEY FEATURES**

- Input resolution settings from PC -VGA, XGA (1024 x 768), SXGA (1280 x 1024), UXGA (1600 x 1200), WUXGA (1920 x 1200) and from Digital Player- 480p up to Full HD 1080p (1920 x 1080)
- Output Resolutions from 480p to 1080p Deep Color 8/10/12
- Audio Supports LPCM 2CH, 6CH, 8CH/AC3/DTS/Dolby Digital Plus/Dolby TruHD & DTS-HD
- Fine tuning and adjustments of contrast, brightness, Saturation and hue
- Preset up to 4 favorite layout options
- Auto EDID detect from the source
- Bezel Correction support for 2x2 Videowall Mode
- USB for Service Mode and Firmware upgrade
- Connection by IR Remote, Telnet or Rs232 for user setup and configuration
- HDMI, HDCP and DVI Compliant
- Factory Reset




# **PANEL DESCRIPTION** HDMI Inputs 2 HDMI Outputs TCP IP Networking Port 4 USB Interface Serial Connector for Control 6 Power Source IR)) WUXGA HDCP

ITEM	SPECIFICATION
Video Bandwidth	225MHz/6.75Gbps
Input port	4x HDMI (Female type), 1xUSB (Service only)
Output port	4 x HDMI (Female type)
Input resolution PC	VGA, XGA (1024 x 768), SXGA (1280 x 1024), UXGA (1600 x 1200), WUXGA (1920 x 1200)
Input resolution Digital Player	480p up to Full HD 1080p (1920 x 1080)
Audio Supported	LPCM 2CH, 6CH, 8CH/AC3/DTS/Dolby Digital Plus/Dolby TruHD & DTS-HD
Output Resolutions	from 480p to 1080p Deep Color 8/10/12 bit source
ESD Protection	Human body model $\pm$ (air-gap discharge), $\pm 4kV$ (contact discharge)
Dimensions (L x W x H)	17" X 7" X 1.7"
Weight	5LBS
Relative Humidity	20 ~ 90% RH (non-condensing)
Power Supply	12V/3A DC (US/EU Standards, CE/FCC/UL certified)



### VIDEO WALLS VIDEO PROCESSORS VIDEO MATRIX SWITCHES EXTENDERS SPLITTERS WIRELESS CABLES & ACCESSORIES



**4x4 Matrix switcher**: This device can input 4 HDMI digital sources and then distribute the video and audio signal to any 4 HDMI HD Monitors. Supported video timings up to 1080p@60Hz Full HD and WUXGA Wide 1920x1200 audio formats up to 7.1CH LPCM AT 192Hz. This device can be configured using the IR Remote, Telnet, Rs232 or Front Panel buttons to set the desired 1-4 output sources.

**Multi Input Splitter**: This device can input 4 HDMI digital sources and then duplicate one source at once to the connected 4 HDMI HD Monitors. This device can be configured using the IR Remote, Telnet, Rs232 or Front Panel buttons to set the desired output source.

**Dual-Viewer**: This device can input 4 HDMI digital sources and then combine, (4) four video signals onto two HD Monitors at Full HD 1080p. This device can be configured using the IR Remote, Telnet, Rs232 or Front Panel buttons to set the desired PAP (Picture Aside Picture).

**Videowall 2x2**: This device can input 4 HDMI digital sources and scale (1) one Input across the (4) four HD monitors in a 2x2 configuration at Full HD 1080p. This device can be configured using the IR Remote, Telnet, Rs232 or Front Panel buttons to set the desired video across the (4) four HD Monitors with Bezel Correction to align the image seamlessly.

Toll Free 1-866-508-0269 Local: +1.716.218.4100 sales@avenview.com

### **USA Head Office**

Avenview Corp. 275 Woodward Avenue Kenmore, NY 14217 Phone: +1.716.218.4100 Fax: +1.866.387-8764

### **Canada Sales Office**

Avenview 151 Esna Park Drive, Unit 11 & 12 Markham, Ontario, L3R 3B1 Phone: 1.905.907.0525 Fax: 1.866.387.8764