

SD-VUE/50A

USB Mini Extender

All you need to extend high-resolution video, fully transparent USB, stereo audio and serial port signals up to 50m over Category 5, 5e, 6 or Level 7 (CATx) cable.

- **High video resolution: 1600x1200@75Hz over 50m**
- **Transparent USB 2.0 (low/full speed only)**
- **Integral 4-port USB hub**
- **Local video output**
- **Emulated VESA DDC**
- **Bi-directional 16-bit stereo audio**
- **Transparent serial port**
- **Local unit powered directly by PC (optional 5V PSU connection)**
- **Status indicator LEDs on RJ45 ports**
- **Rack-mountable (3 units across 1U)**
- **Surge-protected CATx interfaces**



Contents

- Extender Remote unit
- 5V DC universal power supply for Remote unit
- Extender Local unit
- CPU cable set (1.0m) with USB and VGA video (HD15 M-F) connectors
- Serial cable (DB9 M-F)
- Two audio cables (3.5mm stereo)
- IEC power cord
- Quick start guide



Specification

Video

- Maximum Resolution** 1600x1200@75Hz over 50m
Operation at higher resolutions/ refresh rates may be possible at shorter distances
- Video Compatibility** VGA to UXGA, RGB
- Video I/O** 0.7V P-P
- VESA DDC** Emulated DDC for each video channel
Local Unit reports as monitor capable of all resolutions and refresh rates normally used with product. For different resolutions, choose manually in OS and ignore DDC.
- Video Compensation** 2-stage: switch-selectable
- Video Coupling** DC
- Sync I/O** Separate/Composite TTL level
Sync on green
Sync polarity is preserved
- Video In Connectors** HD15 (male)
- Video Out Connectors** HD15 (female)

USB

- USB Compatibility** Transparent USB 2.0 compliant (low/full speed only)
- Connectors(CPU)** 1 x USB B socket
- Connectors (Device)** 4 x USB A socket
- Extension Distance** 50m (nominal)
Maximum distance achievable may vary between 40 and 60m depending on system. Adding external USB hubs may decrease the maximum extension distance by up to 10m for each hub added.
Adding bus-powered hubs in front of the Local Unit is not recommended.

Serial Interface

- Max Baud Rate** 19.2k baud
- Serial Data Format** Transparent
- Signals Transferred** TX, RX, RTS, CTS, DTR,DSR
- Local Connector** DB9 female (DCE)
- Remote Connector** DB9 male (DTE)

Audio Interface

- Description** Bi-directional stereo audio link
- Transmission method** Digitized virtually CD quality audio (16-bit, 38.4kHz)
- Signal levels** Line level (4 Volts Pk-Pk maximum)
- Input Impedance** 47kΩ
- Local Connectors** 2x3.5mm stereo jack socket (Line In & Line Out)
- Remote Connectors** 2x3.5mm stereo jack socket (Line/Mic In & Line Out)
- Microphone Support** May be connected to Remote Unit
Pullup resistor provides bias for condenser microphone
Option to set microphone amplification to +17dB

Power Requirements

- Local Unit** 5V supplied by CPU or powered hub.
Connector available for optional 5V PSU.
- Remote Unit** 5V regulated, 4A (20W) PSU supplied
Universal IEC input
2.1mm DC jack (centre positive)

Size and Shipping Weight

- Local Unit** 120x110x44mm (1U)
- Remote Unit** 138x98x44mm (1U)
- Shipping Weight** 1.8 kg

Environmental

- Operating Temp** 0 to 40 °C
- Storage Temp** -30 to 65 °C
- Relative Humidity** 5-90% non-condensing
- Chassis Construction** Fully shielded. Black painted steel
- Approvals** CE and FCC (Class A)

SD-VUE/50A

USB Mini Extender

Application

