



X124 Single Console

1920 x 1200
WUXGA



Drawer Features & Display Benefits

- ▶ 1U 24" widescreen LCD console drawer
- ▶ Support 1920 x 1200 native **WUXGA** Ultra high resolution
- ▶ PIP & Picture by Picture viewing efficiency
- ▶ Green LED-backlit panel technology
- ▶ 104-key keyboard with either touchpad or trackball
- ▶ MAC or SUN Micro keyboard options available
- ▶ New enhanced aesthetics with molded front handle
- ▶ Front USB port for device access (USB Hub KVM only)

Options

- 3G / HD / SD-SDI Broadcast-grade input (w/ speaker)
- HDMI (w/ speaker)
- DC power : 24V / 48V / 125V / 250V

Ordering Information	Standard (left side open)	Option (right side open)
Model	X124	X124R

Specifications

• LCD Panel

- Size (diagonal) : 24.1" Widescreen TFT
- Max resolution : 1920 x 1200
- Brightness (cd/m2) : 300
- Backlight : LED
- Colors : 16.7 M
- Contrast ratio (typ) : 1000 : 1
- Viewing angle (H/V) : 178° x 178°
- Active area (mm) : 518 x 324
- MTBF (hrs) : 30,000
- Video input : Standard - DVI-D
(single only) Option - HDMI (bundle speaker x 2)

- **Speaker :** Built-in Dual Stereo Speakers
(HDMI only) 2W x 2

- **Casing Color :** Black (RAL 9005)

- **Power Input :** Auto-sensing 100 to 240VAC,
50 / 60Hz

• Power Consumption (single console)

- Sreen on : Max. 40W
- Power saving mode : Max. 5W
- Power button on : Max. 1W

• Environmental

- Operating temperature : 0 to 55°C degree
- Storage temperature : -20 to 60°C degree
- Operating humidity : 20~90%, non-condensing
- Storage humidity : 5 ~90%, non-condensing
- Operating altitude : 16,000 ft
- Non-operating altitude : 40,000 ft
- Shock : 10G acceleration (11ms duration)
- Vibration : 5~500Hz 1G RMS random vibration

• Regulatory

- Safety : FCC & CE certified
- Environmental : RoHS2 & REACH compliant

• Weight (single console)

- Net : 15.3 kgs / 33.7 lbs
- Gross : 19.5 kgs / 42.9 lbs

• Dimensions (single console)

- Product : 441.6 x 700 x 44 mm / 17.4 x 27.6 x 1.73 inch
- Packing : 595 x 910 x 140 mm / 23.4 x 35.8 x 5.5 inch


Console Cable

CX-6


- 6 feet DVI-D console cable (bundle)
- DVI-D + USB, server end
- DVI-D + DB15 (USB KB & MS), console port

Standard Keyboard

Ge G keyboard integrated with touchpad



Gb G keyboard integrated with trackball



Keyboard Options

* US layout only

Me Mac keyboard with touchpad



Mb Mac keyboard with trackball

Se S keyboard with touchpad

Sb S keyboard with trackball



Supporting layouts

America		United States
EMEA		United Kingdom
		Germany
		France
		Spain
		Norway
		Italy
		Russia
		Switzerland
		Netherlands
		Portugal
Asia		China
		Japan
		Korea
		Arabia
		Turkey

1U 24" High Resolution LCD KVM Drawer



- Dimensions (with KVM)**
 Product : 441.6 x 800 x 44 mm / 17.4 x 31.5 x 1.73 inch
 Packing : 595 x 910 x 140 mm / 23.4 x 35.8 x 5.5 inch
 - Weight**
 Net : 16.1 kgs / 35.4 lbs
 Gross : 22 kgs / 48.4 lbs
 - Power Consumption with KVM integration :**
 Screen on : Max. 65W
 Power saving mode : Max. 30W
 - Casing Color :** Black (RAL 9005)
- * For details, please refer to our KVM rear kit user manuals.

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-MKVM-KIT.pdf

For right side open - Add **R** at the end of the model no.
sample : X124-MIP1624R

Matrix DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	1	1	X124 - MIP813	X124 - MIP1613	-
	1	1	2	X124 - MIP824	X124 - MIP1624	-
	1	1	0	X124 - M802	X124 - M1602	-
	1	2	0	X124 - M803	X124 - M1603	-
	1	3	0	X124 - M804	X124 - M1604	-

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-SKVM-KIT.pdf

Combo DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	0	1	X124 - IP802	X124 - IP1602	-
	1	1	0	X124 - 802	X124 - 1602	-
	1	0	0	X124 - S801	X124 - S1601	-

Combo DB-15 KVM Cable : CE-6 / 10 / 15 (6, 10 or 15 ft)

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-DVIKVM-KIT.pdf

For right side open - Add **R** at the end of the model no.
sample : X124-1201DR

DVI-D KVM	Local	Remote	IP	12-port	-	-
	1	0	0	X124 - 1201D	-	-

DVI-D KVM Cable : CI-6 / 15 (6 or 15 ft)

www.austin-hughes.com/support/usermanual/cyberview/UM-CV-USBKVM-KIT.pdf

For right side open - Add **R** at the end of the model no.
sample : X124-801HR

USB Hub DB-15 KVM	Local	Remote	IP	8-port	16-port	32-port
	1	0	1	X124 - IP802H	X124 - IP1602H	-
	1	1	0	X124 - 802H	X124 - 1602H	-
	1	0	0	X124 - 801H	X124 - 1601H	-

USB KVM Cable : CB-6 / 10 / 15 (6, 10 or 15 ft)