

CL1008/1016


Slideaway™ LCD KVM Switch

The CL1008 / CL1016 LCD KVM Switch series are control units that allow access to multiple computers from a single keyboard, video, and mouse (KVM), console. A single CL1008 or CL1016 can control up to 8 or 16 computers. As many as 15 additional KVM switches can be daisy-chained to the CL1008 / CL1016, so that up to 256 computers can all be controlled from a single KVM console.

The CL1008 / CL1016 offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 17" LCD monitor, and touchpad in a 1U rack-mountable sliding housing.



Setup



Features

- KVM console with 17" LCD monitor in a sliding housing with top and bottom clearance for smooth operation in a 1U high system rack
- LCD module rotates up to 115 degrees for a more comfortable viewing angle
- Standard rack mount kit included – optional Easy Rack Mounting (single person installation) rack mount kit available (requires separate purchase)
- Daisy-chain up to 15 additional units – control up to 256 computers
- No software required – convenient computer selection via hotkeys and mouse driven intuitive on screen display (OSD) menus
- Auto Scan feature for monitoring user-selected computers
- Broadcast support – commands from the keyboard can be broadcast to all available computers on the installation
- Hot pluggable – add or remove computers without having to power down the switch
- Two level password security – only authorized users view and control the computers; up to four users plus an administrator with separate profiles for each
- Video settings of attached computers are automatically adjusted for optimal output to the LCD monitor
- Upgradable firmware
- Keyboard Language support: English(US); English(UK); German; German(Swiss); French; Spanish; Traditional Chinese; Japanese; Korean; Swedish; Italian; Russian; Hungarian

Rack Mount Kit	Depth (cm)
Long (Optional)	68 - 105
Short (Standard)	42 - 82

Easy Installation Rack Mount Kit	Depth (cm)
Long (Optional)	68 - 105
Short (Optional)	52 - 70

Specifications

Function		CL1008	CL1016	
Computer Connections	Direct	8	16	
	Max	128 (via Daisy-chain)	256 (via Daisy-chain)	
Port Selection		OSD; Hotkey; Pushbutton		
Connectors	KVM Ports	8 x SPHD Female (Yellow)	16 x SPHD Female (Yellow)	
	Daisy-Chain	1 x DB-25 Male		
	FW Upgrade	1 x RJ-11 Female		
	Power	1 x 3-prong AC socket		
Switches	Reset	1 x Semi-recessed pushbutton		
	Power	1 x Rocker		
	F/W Upgrade	1 x Slide		
	LCD Adjust	4 x Pushbutton		
LEDs	Port Selection	8 x Pushbutton	16 x Pushbutton	
	On Line	8 (Orange)	16 (Orange)	
	Selected	8 (Green)	16 (Green)	
	Power		1 (Dark Green)	
		Num	1 (Green)	
		Caps	1 (Green)	
Scroll	1 (Green)			
Emulation	Keyboard / Mouse	PS/2		
Video	17" LCD	1280 x 1024 @ 75 Hz; DDC2B		
Scan Interval (OSD Select)		1-255 Seconds		
I/P Rating		100-240V AC; 50/60Hz; 1A		
Power Consumption	17" LCD	120V; 30W 230V; 37W		
Environment	Operating Temp.	0-40°C		
	Storage Temp.	-20-60°C		
	Humidity	0-80% RH-condensing		
Physical Properties	Housing	Metal+Plastic		
	Weight	17" LCD	13.10 kg	13.30kg
	Dimensions (D x W x H)		63.40 x 48.00 x 4.40 cm (19"/1U)	

* The specifications and pictures are subject to change without notice.