

# VGA / Audio Cat 5 Extender


## VE170 / VE170Q

- The VE170 VGA / Audio Cat 5 Extenders, consisting of a transmitter (VE170T) and receiver (VE170R), are cost-effective and efficient solutions for sending and receiving high quality audio/video content over long distances. Simply connect the transmitter to the receiver via one Cat 5e cable, and a VGA display or projector can be located up to 300 m (1000 ft) away from the video source.

The VE170Q package consists of a transmitter (VE170T) and receiver (VE170RQ), which includes ATEN's patented Deskew™ technology that supports resolutions up to 1280 x 1024 @ 300 m, and features manual synchronization of the RGB signals and correction of color phase and timing errors that occur over long distances.


The VE170 / VE170Q VGA / Audio Cat 5 Extenders provides a flexible solution which is ideal for any professional A/V installation that requires multimedia content to be delivered over a long distance.

VE170 Package		VE170Q Package	
VE170T Transmitter	VE170R Receiver	VE170T Transmitter	VE170RQ Receiver with Deskew



## Features

- Connects a transmitter and receiver via Cat 5e cable
- Supports one local and one remote VGA display
- Long distance transmissions – up to 300 m
- Deskew™ (VE170Q) – automatically synchronizes the time delay of RGB signals to compensate for distance
- Adjustable Gain Control – signal strength can be manually adjusted via video gain or video compensation tuners
- Audio supported (mono)
- Built-in ESD protection
- Rack-mountable



## Specifications

Function	VE170R	VE170RQ	VE170T
<b>Video Input</b>			
Interfaces	N/A	N/A	1 x HDB-15 Male (Blue)
Impedance	N/A	N/A	75 Ω
Max. Distance	N/A	N/A	1.8 m
<b>Video Output</b>			
Interfaces	1 x HDB-15 Female (Blue)	1 x HDB-15 Female (Blue)	1 x HDB-15 Female (Blue)
Impedance	75 Ω	75 Ω	75 Ω
<b>Video</b>			
Max. Bandwidth	300 MHz	300 MHz	300 MHz
Max. Resolutions / Distance	Up to 1920 x 1200 @ 30 m; 1024 x 768 @ 300 m	Up to 1920 x 1200 @ 150m; 1280 x 1024 @ 300 m	Up to 1920 x 1200 @ 30 m; 1024 x 768 @ 300 m
<b>Audio</b>			
Output	1 x Mini Stereo Jack Female (Green)	1 x Mini Stereo Jack Female (Green)	1 x Mini Stereo Jack Female (Green)
Input	N/A	N/A	1 x Mini Stereo Jack Female (Green)
<b>Power</b>			
Connectors	1 x DC Jack	1 x DC Jack	1 x DC Jack
Consumption	5.3 VDC, 3.66W	5.3 VDC, 4.82W	5.3 VDC, 2.66W
<b>Environmental</b>			
Operating Temperature	0° to 50° C	0° to 50°C	0° to 50°C
Storage Temperature	-20° to 60°C	-20° to 60°C	-20° to 60°C
Humidity	0 - 80% RH, Non-Condensing	0 - 80% RH, Non-Condensing	0 - 80% RH, Non-Condensing
<b>Physical Properties</b>			
Housing	Metal	Metal	Metal
Weight	0.24 kg	0.24 kg	0.24 kg
Dimensions (L x W x H)	12.77 x 9.04 x 2.26 cm	12.77 x 9.04 x 2.26 cm	12.77 x 9.04 x 2.26 cm

## ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com

Publish Date: 11/2016 V1.0



© Copyright 2016 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.